

Friday 27 May 2022 - Afternoon

GCSE (9-1) Computer Science

J277/02 Computational thinking, algorithms and programming

Time allowed: 1 hour 30 minutes

• a calculator	
 Please write clearly in black ink. Do not writ	te in the barcodes.
Centre number	Candidate number
First name(s)	

INSTRUCTIONS

Last name

- Use black ink.
- Write your answer to each question in the space provided. If you need extra space use the lined pages at the end of this booklet. The question numbers must be clearly shown.
- · Answer all the questions.

INFORMATION

- The total mark for this paper is **80**.
- The marks for each question are shown in brackets [].
- This document has 20 pages.

ADVICE

Read each question carefully before you start your answer.

© OCR 2022 [601/8355/X] DC (ST/CT) 319567/4 R

OCR is an exempt Charity

Turn over

Answer all the questions.

SECTION A

1 (a) Tick (✓) **one** box in each row to identify whether the OCR Reference Language code given is an example of selection or iteration.

OCR Reference Language code	Selection	Iteration
<pre>for i = 1 to 10 print(i) next i</pre>		
<pre>while score != 0 playgame() endwhile</pre>		
<pre>if playerHit() then score = 0 endif</pre>		
<pre>switch bonus: case 0: score = 9 case 1: score = 7 case 2: score = 5 endswitch</pre>		

(b)	Write pseudocode to increment the value held in the variable score by one.	
(c)	State the name of each of the following computational thinking techniques.	. [1]
	Breaking a complex problem down into smaller problems.	
	Hiding or removing irrelevant details from a problem to reduce the complexity.	
		[2]

[4]


2 A fast food restaurant offers half-price meals if the customer is a student or has a discount card. The offer is not valid on Saturdays.

A computer system is used to identify whether the customer can have a half-price meal.

The table identifies the three inputs to the computer system:

Input	Value					
Α	Is a student					
В	Has a discount card					
С	The current day is Saturday					

- (a) The logic system P = (A OR B) AND NOT C is used.
 - (i) Complete the following logic diagram for **P = (A OR B) AND NOT C** by drawing one logic gate in each box.



1	ii۱	A truth table can	he	produced	for	this	logic	circuit
١		A trutti table carr		produced	101	นเมือ	logic	on cuit.

(iii) State how many rows (excluding any headings) would be required in a truth table for the logic expression:

P = (A OR B) AND NOT C

......[′ © OCR 2022 Turn over

[3]

- (b) The restaurant needs an algorithm designing to help employees work out if a customer can have a half price meal or not. It should:
 input required data
 decide if the customer is entitled to a discount
 - output the result of the calculation.

Design the algorithm using a flowchart.					

(c)	The restaurant adds a service charge to the cost of a meal depending on the number of people at a table. If there are more than five people 5% is added to the total cost of each meal.
	Customers can also choose to leave a tip, this is optional and the customer can choose between a percentage of the cost, or a set amount.
	Identify all the additional inputs that will be required for this change to the algorithm.

(d) Each member of staff that works in the restaurant is given a Staff ID. This is calculated using the following algorithm.

01	<pre>surname = input("Enter surname")</pre>
02	<pre>year = input("Enter starting year")</pre>
03	<pre>staffID = surname + str(year)</pre>
04	while staffID.length < 10
05	staffID = staffID + "x"
06	endwhile
07	<pre>print("ID " + staffID)</pre>

(i) Define the term **casting and** give the line number where casting has been used in the algorithm.

Definition	 	 	
Line number	 	 	
			[2]

(ii) Complete the following trace table for the given algorithm when the surname "Kofi" and the year 2021 are entered.

You may not need to use all rows in the table.

Line number	surname	year	staffID	Output
01	Kofi			
02		2021		

3 A program stores the following list of positive and negative numbers. The numbers need sorting into ascending order using a merge sort.

45	12	-99	100	-13	0	17	-27

(a) The first step is to divide the list into individual lists of one number each. This has been done for you.

Complete the merge sort of the data by showing each step of the process.

45

12

-99

100

-13

0

17

-27

[3]

(b)	Once the numbers are in order, a binary search can be run on the data.
	Describe the steps a binary search will follow to look for a number in a sorted list.
	[4]
(c)	A linear search could be used instead of a binary search.
	Describe the steps a linear search would follow when searching for a number that is not in the given list.
	[2]

4 Jack is writing a program to add up some numbers. His first attempt at the program is shown.

```
a = input("Enter a number")
b = input("Enter a number")
c = input("Enter a number")
d = input("Enter a number")
e = input("Enter a number")
f = (a + b + c + d + e)
print(f)
```

(a) Give two ways that the maintainability of this program could be improved.

1	
•	
2	
_	
•	[7]

- **(b)** Jack's program uses the addition (+) arithmetic operator. This adds together two numbers.
 - (i) State the purpose of each of the arithmetic operators in the table.

Arithmetic operator	Purpose
*	
/	

[2]

(ii) Complete the description of programming languages and translators by writing the correct term from the box in each space.

continues	crashes	debugging	error	executable
high-level	interpreter	language	low-level	many
no	one	stops	with	without

compiler.	[5]
The file produced can be run the	
an error report. The code will not run until there are errors.	
A second type of translator is a compiler. This converts all of the code and produces	
helpful when debugging code.	
found, and when corrected continues running from the same position. This translator is	S
executes it, before moving to the next line. It when an error is	S
One type of translator is an interpreter. This converts one line of code and then	
a translator.	
translated into assembly or machine code before it can be executed. This is done using	g
Jack writes his program in a language. This needs to be	

(c) Jack decides to improve his program. He wants to be able to input how many numbers to add together each time the algorithm runs, and also wants it to calculate and display the average of these numbers.

Write an algorithm to:

- ask the user to input the quantity of numbers they want to enter and read this value as input
- repeatedly take a number as input, until the quantity of numbers the user input has been entered
- been entered
 calculate and output the total of these numbers

calculate and output the average of these numbers.

re
[6

SECTION B

We advise you to spend at least 40 minutes on this section.

Some questions require you to respond using either the OCR Exam Reference Language or a high-level programming language you have studied. These are clearly shown.

- 5 Customers at a hotel can stay between 1 and 5 (inclusive) nights and can choose between a basic room or a premium room.
 - (a) A typical booking record is shown in the table:

firstName	Amaya	
surname	Taylor-Ling	
nights	3	
room	Premium	
stayComplete	False	

(i)	State the most appropriate data type for the following fields:	
	Nights	
	Room	[2
(ii)	Give the name of one field that could be stored as a Boolean data type.	L
		[1 ⁻

(iii) Booking records are stored in a database table called TblBookings.

The following SQL statement is written to display all customer bookings that stay more than one night.

SEI	LΕC	CT	AL]	L		
FRO	MC	Tk	olBo	ool	kir	ıgs
ΙF	Νj	gh	nts	<	1	

The SQL statement is incorrect.	
Rewrite the SQL statement so that it is correct.	
	41

Turn over © OCR 2022

- **(b)** When a new booking is recorded, the details are entered into a program to validate the values. The following criteria are checked:
 - firstName and surname are not empty
 - room is either "basic" or "premium"
 - nights is between 1 and 5 (inclusive).

If any invalid data is found "NOT ALLOWED" is displayed. If all data is valid "ALLOWED" is displayed.

(i) Complete the following program to validate the inputs.

You must use either:

- OCR Exam Reference Language, or
- a high-level programming language that you have studied.

<pre>firstName = input("Enter a first name")</pre>
<pre>surname = input("Enter a surname")</pre>
<pre>room = input("Enter basic or premium")</pre>
<pre>nights = input("Enter between 1 and 5 nights")</pre>
stayComplete = False

	•
[5]	

(ii) Complete the following test plan to check whether the number of nights is validated correctly.

Test data (number of nights)	Type of test	Expected output
2		ALLOWED
	Boundary	ALLOWED
	Erroneous / Invalid	NOT ALLOWED

[3]

- (c) A Basic room costs £60 each night. A Premium room costs £80 each night.
 - (i) Create a function, newPrice(), that takes the number of nights and the type of room as parameters, calculates and returns the price to pay.

You do **not** have to validate these parameters.

You must use either:	
 OCR Exam Reference Language, or a high-level programming language that you have studied. 	
	• •
[4	ij
Write program code, that uses $newPrice()$, to output the price of staying in a Premiur room for 5 nights.	n
You must use either : OCR Exam Reference Language, or a high-level programming language that you have studied.	
r	7

(ii)

(d) The hotel has nine rooms that are numbered from room 0 to room 8.

The number of people currently staying in each room is stored in an array with the identifier room.

The index of room represents the room number.

Array room

Index	0	1	2	3	4	5	6	7	8
Data	2	1	3	2	1	0	0	4	1

The following program counts how many people are currently staying in the hotel.

```
for count = 1 to 8
    total = 0
    total = total + room[count]
next count
print(total)
```

When tested, the program is found to contain two logic errors.

	•••
[2	2]

(e) The hotel car park charges £4 per hour. If the car is electric, this price is halved to £2 per hour.

Write an algorithm to:

- take as input the number of hours the user has parked and whether their car is electric or not
- calculate and output the total price
- repeat continually until the user enters 0 hours.

Vall	munt		aith	~ "
rou	must	use	eim	er.

 OCR Exam Reference Language, or a high level programming language that you have studied.

END OF QUESTION PAPER

.....[6]

19

ADDITIONAL ANSWER SPACE

If additional space is required, you should use the following lined page(s). The question number(s) must be clearly shown in the margin(s).						
	<u> </u>					

 ,	 	
 <u> </u>	 	



Copyright Information

OCR is committed to seeking permission to reproduce all third-party content that it uses in its assessment materials. OCR has attempted to identify and contact all copyright holders whose work is used in this paper. To avoid the issue of disclosure of answer-related information to candidates, all copyright acknowledgements are reproduced in the OCR Copyright Acknowledgements Booklet. This is produced for each series of examinations and is freely available to download from our public website (www.ocr.org.uk) after the live examination series.

If OCR has unwittingly failed to correctly acknowledge or clear any third-party content in this assessment material, OCR will be happy to correct its mistake at the earliest possible opportunity.

For queries or further information please contact The OCR Copyright Team, The Triangle Building, Shaftesbury Road, Cambridge CB2 8EA.

OCR is part of Cambridge University Press & Assessment, which is itself a department of the University of Cambridge.

© OCR 2022